




PRODUCT MANUAL

HOT HARMONICA


INSTALLATION

Please install the Hot Harmonica according to the illustrations.

Suggested installation for small harmonicas: Outside on the metal casing.



Suggested installation for bigger harmonicas: Inside the instrument on the reed block.



PROCEDURE

Please make sure the area where you want to attach the transducer is dust- and grease free. For internal mounting, please unscrew casing and slightly sand the gluing area. Wipe the spot where you will attach the transducer with rubbing alcohol and let dry. Apply super glue to the metal side of the transducer disc and press on the clean attachment spot.

Attach the mini jack according to illustration.

INFORMATION

Even though the harmonica belongs to the wind instruments group, a class of instruments that are not naturally apt for transducer application, you will achieve really good results with the Hot Harmonica.

Important: Please, avoid tapping on the instrument with your fingers while playing, unless you want to amplify this tapping.

If you need to remove the transducer, hold the pickup in place with your finger and carefully slide a thin knife blade underneath it to lift the transducer up. Don't use a serrated knife. Any remaining adhesive can be rubbed or cleaned off.

Important: Never pull off a transducer by its cable! Use a knife for removal.

TECHNICAL DATA

Transducer Head Diameter: 1/2"

Height: 1/32"

Impedance: High ohmic

Length of Connection Cable: 1 inch (2.5 cm)

Output: RCA Male